

本製品について

本製品は44鍵盤ハーモニカに、ピックアップマイクを内蔵した楽器で、アンプやエフェクター等の外部機器との接続が可能です。またアコースティック楽器として、単体での演奏にも十分な音量と表現を実現しました。

- 幅広い曲に対応する44鍵盤
- ピックアップマイク搭載
- 吹く息の強弱に素直に反応するテーパーリード
- プレイスタイルに合わせて選べる3種類の唄口を付属
- 長さ調整可能なハンドストラップ

仕様

鍵 数・音 域：アルト44鍵 c～g³
仕 上：リン青銅テーパーリード
リードプレートメッキ仕上
外 部 端 子：外部出力(標準ジャック、マイクレベル)
マ イ ク：小型ダイナミックマイク内蔵
コントロール：ボリューム
寸 法：563×106×52mm
重 量：1127g(PRO-44H)
1213g(PRO-44HP)
付 属 品：ショートマウスピース・フレキシブルマウス
ピース・L字ジョイントロングマウスピース・
セルベット・ソフトケース

FEATURES

The HAMMOND 44 incorporates a high-end lavalier microphone inside and is capable of connection to external devices such as an amplifier or external effects unit. Of course you can play the HAMMOND 44 as an acoustic melodeon. Its advanced design allows powerful volume and expressive performance.

EXCLUSIVE FEATURES

- * High-Quality on-board lavalier microphone
- * 3 kinds of associated mouthpieces, which
- * Tapered reeds, which accurately allows performance versatility
- respond to your breath strength
- * adjustable hand strap

SPECIFICATIONS

Key : c～g³, Alto 44 keys
Reed : Phosphor bronze tapered reeds
Reed plate : brass
1/4 inch output jack : standard 1/4
Microphone : internal dynamic lavalier
Control : Volume
Dimension : 22.17"x 4.17"x 2.05", (563 x 106 x 52 mm)
Weight : PRO-44H:2.48lb (1127g) / PRO-44HP:2.67lb(1213g)
Accessory : special short mouthpiece MP-141, flexible mouthpiece,
mouthpiece with tube and L-shaped joint,
cleaning cloth, soft case

HAMMOND 44 Limited Warranty

The Hammond 44 is warranted to be free of manufacturing defects for one (1) year from the original date of purchase. If the Hammond 44 is found to contain manufacturing defects, it will be at Hammond's discretion, be repaired or replaced at no charge providing the Hammond 44 is shipped pre-paid to the Hammond service Center. A copy of the original purchase receipt is required.

The Hammond 44 is not warranted for normal wear and tear, physical damage, abuse or modifications not performed by Hammond.

Normal maintenance is not covered by this warranty. This includes normal wear pertaining to parts such as reeds (including tuning).

The vinyl tube that is connected to your L Joint Long Mouthpiece may develop a crack over a long period of use. This condition is considered normal and is not replaceable free of charge under your warranty.

CAUTION

To avoid the risk of damage please read and obey the following instructions.

Do not attempt to open or modify this instrument.

Do not put any foreign object or liquids inside.

Physical shocks caused by dropping, bumping or placing heavy objects on the instrument can result in scratches and more serious damage.

Do not use or store this instrument in or near water or high-humidity atmosphere.

Do not use or store this instrument in or near any heat sources such as radiators, heat registers, stoves or other apparatus (including amplifiers) that product heat.

Do not use or store this instrument in a dusty place.

Clean this instrument with a dry soft cloth. Do not use alcohol, thinner's or petro-chemical-based polishes.

Release all moisture from this instrument after use and store safely.

Return Procedure:

If it becomes necessary to return your HAMMOND 44, you must FIRST contact one of the following for return authorization. The Hammond 44 will NOT be accepted at the service center without this authorization.

In the United States Contact: HAMMOND SUZUKI USA, INC.

In the EU countries Contact: HAMMOND SUZUKI EUROPE B.V.

In all other Countries Contact: Original retailer where product was purchased for additional warranty details.

- This Warranty gives you specific legal rights, and you may also have other rights which may vary from state to state or from country to country. -

株式会社 鈴木楽器製作所

〒430-0852 静岡県浜松市中区領家2-25-12 ☎(053)461-2325



メールでのお問い合わせは下記まで
info@suzuki-music.co.jp

HAMMOND SUZUKI USA, INC.

733 Annoreno Drive
Addison, Illinois 60101 USA

Tel: (630)543-0277

Fax: (630)543-0279

E-mail:info@hammondorganco.com

Website:www.hammondorganco.com

HAMMOND SUZUKI EUROPE B.V.

Ir. D. S. Tuynmanweg 4 A
4131 PN Vianen, The Netherlands

Tel: 0031-347-370594

Fax: 0031-347-370621

E-mail:info@hammondsuzuki.com


Website:www.hammondsuzuki.com




1108-2B-APR-MM-131-B
00457-00014

1)各部の名称とはたらき

本体



付属品



2)外部機器との接続について


ご注意

高音域側のサイドカバーをスピーカーに近づけたり、音量を上げすぎたり、音を歪ませたりするとハウリングを起こしやすくなりますので注意してください。

アンプ、エフェクターその他の外部機器の入力仕様は、以下を推奨します。

- ◎入力インピーダンス: 10kΩ以上
- ◎基準入力レベル : -30dBV

接続例



3)お手入れについて

【水分の抜き方】


楽器の特性上、本製品の内部に水分がたまります。水分がたまると音が鳴りにくくなることがありますので、演奏中もこまめに水分を抜いてください。
だ液抜きレバーを押したまま①、マウスピース側から息を強く吹き込むと②、だ液抜きレバーから水分が抜けます。③

水分をしっかりと抜いたら、付属のセルベットで汚れを拭き、ケースに入れて保管してください。




1) PARTS AND ACCESSORIES

Body



Accessories



2) CONNECTING TO AMPLIFIER AND EXTERNAL EFFECTS


Notice: To prevent feedback,

- a) keep the treble side away from speaker
- b) use a moderate volume
- c) do not overdrive preamp to attempt distortion

Information to choose the amplifier or external effects

Input impedance : over 10K Ohms
Standard input level : -30 dBV

Connection example



3) HOW TO CLEAN

How to release moisture

Because of the Melodion's structure, moisture from your breath can build up inside. The sound quality will deteriorate as the moisture builds up. Please release this moisture frequently, even during a performance.

Moisture release procedure :

- a) Press the spit-valve and hold open
- b) Blow strongly from mouthpiece side without pressing any keys.
- c) Moisture is released from the spit-valve. Release after moisture is cleared.

Release moisture often, especially before putting the instrument away. Clean the instrument with cleaning cloth and store it in the case.

